

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Jung Jin PARK  
 Docket: 13424.7US01  
 Title: DEVICE AND METHOD FOR SCRAMBLING/DESCRAMBLING VOICE AND DATA FOR MOBILE COMMUNICATION SYSTEM

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number EL674897480US

Date of Deposit: November 21, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C 20231.

By Brant Miles  
 Name: Brant Miles

BOX PATENT APPLICATION  
 Assistant Commissioner for Patents  
 Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 19 pgs; 12 claims; Abstract 1 pgs.  
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 6 sheets of formal drawings
- ☒ Certified copy of a Republic of Korea application, Serial No. 1999-58711, filed December 17, 2000, the right of priority of which is claimed under 35 U.S.C. 119
- ☒ A signed Combined Declaration and Power of Attorney
- ☒ Assignment of the invention to Hyundai Electronics Ind. Co. Ltd., Recordation Form Cover Sheet
- ☒ A check in the amount of \$870.00 to cover the Filing Fee
- ☒ A check for \$40.00 to cover the Assignment Recording Fee.
- ☒ Other: Information Disclosure Statement, Form 1449, 3 References; Communication Regarding Submission of Priority Document
- ☒ Return postcard

**CLAIMS AS FILED**

Number of Claims Filed	In Excess of:	Number Extra	Rate	Fee
<b>Basic Filing Fee</b>				\$710.00
<b>Total Claims</b>				
12	20	0	0.00	\$0.00
<b>Independent Claims</b>				
5	3	2	80.00	\$160.00
<b>MULTIPLE DEPENDENT CLAIM FEE</b>				\$0.00
<b>TOTAL FILING FEE</b>				<b>\$870.00</b>

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2725. A duplicate of this sheet is enclosed.

MERCHANT & GOULD P.C.  
 P.O. Box 2903, Minneapolis, MN 55402-0903  
 (612) 332-5300

By: Curtis B. Hamre  
 Name: Curtis B. Hamre  
 Reg. No.: 29,165  
 Initials: CBH/kas



PTO TRANSMITTAL - NEW FILING)

11/21/00  
 jc806 U.S. PTO

jc903 U.S. PTO  
 09/718220  
 11/21/00

# DEVICE AND METHOD FOR SCRAMBLING/DESCRAMBLING VOICE AND DATA FOR MOBILE COMMUNICATION SYSTEM

## BACKGROUND OF THE INVENTION

### 5    1. Field of the Invention

The present invention relates to vocoding voice and data in a mobile communication system and, more particularly, to a device and method for scrambling/descrambling voice and data for a mobile communication system whereby communication signals on a cable channel can be scrambled and descrambled  
10    irrespective of the operational mode of a system vocoder in a digital mobile communication system during voice data transmission between mobile stations with the vocoder.

### 2. Description of the Related Art

Generally, voice is transmitted after compression in a digital mobile  
15    communication system in order to support a large number of mobile stations within a limited capacity of radio channels. For voice compression, there is used a voice scrambling algorithm, normally, a vocoding algorithm in the field of the mobile communication system because the vocoding algorithm is characterized by low data rate and voice quality for the cable network. The vocoding algorithm, which is an error-  
20    containing algorithm, produces more errors between the restored voice and the original one with an increase in the number of iterative compression and restorations. That is, the tone quality of the restored voice deteriorates.

Fig. 1 is a diagram for explaining interval-based transmission of voice and data

between mobile stations in a general mobile communication system.

As illustrated in the figure, when an originating mobile station 1 compresses voice and transmits the compressed voice to a transport station 2 in the form of packet, then a vocoder (not shown) in the transport station 2 restores the packet to data in the PCM (Pulse Code Modulation) form. The PCM data are sent to a transport station 2' serving a target mobile station 1' via an exchange 3 and then recompressed at the vocoder provided in the transport station 2'. Here, the transport station 2 includes a base station controller and a base station. The compressed packet is sent to the target mobile station 1' via a radio channel.

The mobile station 1' restores the received packet with an internal vocoder. Through these procedures, the mobile station can receive voice from the originating mobile station.

Finally, the voice undergoes two vocoding steps during transmission between the two mobile stations. In this event, the voice packet compressed and transmitted from the originating mobile station 1 via a radio channel is packet-bypassed at the system vocoder, thereby reducing the number of vocoding steps and decreasing deterioration of tone quality. This packet bypass process is also utilized in data transmission. Here, between the mobile station 1 or 1' and the transport station 2 or 2' is the radio channel interval and between the transport station 2 or 2' and the exchange 3 is the cable channel interval.

Now, a description will be given to a device for vocoding voice signals according to prior art with reference to Fig. 2.

Fig. 2 presents the patterns of a packet bypassed at the vocoder in a general mobile communication system, wherein Fig. 2a shows the format of the bypassed voice

packet and Fig. 2b shows the format of the bypassed data packet. Fig. 3 is a schematic block diagram of a vocoding device in the respective operational modes in a mobile communication system according to prior art.

First, the vocoding device in the mobile communication system includes a  
5 vocoder 20 and an upper processor 10. The upper processor 10 includes the entire of the transport stations 2 and 2' and the exchange 3, except the vocoder 20.

The vocoder 20 includes first to fourth mode switching blocks 22, 26, 27 and 31 and first to sixth vocoding processors 23, 24, 25, 28, 29 and 30 for performing a mode-based vocoding.

10 The above-configured vocoding device in the mobile communication system according to the prior art operates in three operational modes during data transmission between the mobile stations.

The first operational mode is enabled when the vocoders in the mobile stations are distinct, for example, 8 Kbps EVCR (Enhanced Variable Code Rate) and 13 Kbps  
15 QCELP (Qualcomm Code Excited Linear Predictive) vocoders, in which mode the system vocoders perform a normal vocoding process, i.e., voice scrambling and descrambling. In this event, the pattern of the transmission data is packet data on the radio channel (i.e., a transmission line between the mobile station and the system vocoder), and PCM data on the cable channel (i.e., a transmission line between the  
20 system vocoders between which the exchange is interposed).

The second operational mode is enabled when the vocoders in the mobile stations are identical, for example, EVCT vocoders or QCLP vocoders, in which case the system vocoders operate in a voice packet bypass mode. In this event, the pattern of the

transmission data is packet data on the radio channel, and bypassed voice packet data as shown in Fig. 2a on the cable channel.

The third operational mode is enabled during data transmission between the mobile stations, in which mode the system vocoders operate in a data packet bypass mode. In this event, the pattern of the transmission data is packet data on the radio channel, and bypassed data packet as shown in Fig. 2b on the cable channel.

The conventional vocoding system operating in the above-stated three operational modes is illustrated in Fig. 3.

As show in Fig. 3, the vocoder 20 receives mode information "E" from the upper processor 10 and operates in the corresponding mode under the control of the mode controller 21.

For example, when the vocoder 20 receives the first mode information from the upper processor 10, the mode controller 21 switches the switching blocks 22 and 26 to the first vocoding processor 23, which vocodes voice packet data transferred from the originating mobile station via a radio channel "A" into PCM data and sends the PCM data to the exchange via a cable channel "C". The mode controller 21 also switches the switching blocks 27 and 31 to the fourth vocoding processor 28, which vocodes the PCM data transferred from the exchange via a cable channel "D" into packet data and sends the packet data to the target mobile station via a radio channel "B".

If the vocoder 20 receives the second mode information from the upper processor 10, the mode controller 21 switches the switching blocks 22 and 26 to the second vocoding processor 24, which bypasses voice packet data transferred from the originating mobile station via the radio channel "A" and sends the bypassed voice packet

data to the exchange via the cable channel "C". The mode controller 21 also switches the switching blocks 27 and 31 to the fifth vocoding processor 29, which bypasses voice packet data transferred from the exchange via the cable channel "D" and sends the bypassed voice packet data to the target mobile station via the radio channel "B".

5           When the vocoder 20 receives the third mode information from the upper processor 10, the mode controller 21 switches the switching blocks 22 and 26 to the third vocoding processor 25, which bypasses data packet transferred from the originating mobile station via the radio channel "A" and sends the bypassed data packet to the exchange via the cable channel "C". The mode controller 21 also switches the switching  
10       blocks 27 and 31 to the sixth vocoding processor 30, which bypasses data packet transferred from the exchange via the cable channel "D" and sends the bypassed data packet to the target mobile station via the radio channel "B".

As such, the vocoder 20 communicates packets on the radio channels "A" and "B" as well as mode information with the upper processor 10 to perform an adequate  
15       processing based on the mode information, and communicates bypassed packet data and PCM data as shown in Fig. 2 on the cable channels "C" and "D" based on the operational mode.

The upper processor 10 not only controls the vocoder 20 but also enables packet communication between the mobile station and the system vocoder through the radio  
20       channels.

However, the vocoding system according to the prior art involves a problem in that the voice data on the cable channels are susceptible to overhearing while the system vocoders is operating in the respective modes.

For example, in the first operational mode, i.e., normal vocoding mode, the PCM data on the cable channels are ready to be overheard by an overhearing instrument.

In the second operational mode, i.e., voice packet bypass mode, the bypassed voice packet data are not easy to overhear by a general PCM overhearing method but  
5 susceptible to overhearing, because the voice packets are positioned in the predefined fields in a given order, as shown in Fig. 2a, with a limited number of cases for finding a specific voice packet among the entire bypassed voice packets at a position.

In the third operational mode, i.e., data packet bypass mode, the data packets can be extracted simply by eliminating a flag field having the same pattern, because the  
10 bypassed data packets iteratively appear on the cable channels, as shown in Fig. 2b.

### **SUMMARY OF THE INVENTION**

It is, therefore, an object of the present invention to provide a device for scrambling/descrambling voice and data in a mobile communication system, in which a transmitter system vocoder has an scrambling function to scramble a communication  
15 signal on a cable channel and a receiver system vocoder has a descrambling function to descramble the scrambled data, thereby preventing overhearing of the voice data.

It is another object of the present invention to provide a method for scrambling/descrambling voice and data corresponding to the operation of the vocoder.

Specifically, the object of the present invention is to provide a device and method  
20 for scrambling/descrambling voice and data in a mobile communication system, in which the system vocoders are provided with a scrambler and a descrambler to scramble a communication signal and descramble the scrambled signal using the same scrambling key received from the upper processor, in order to prevent overhearing of voice and data

drain on cable channels.

To achieve the above object of the present invention, in a voice/data vocoding device for a mobile communication system, a device for scrambling voice and data in the mobile communication system includes: a controller for generating an operational mode  
5 control signal to control an operational mode of the voice and data, a scrambling key feeding control signal to control data scrambling, and a sync signal generation control signal; an operational mode processor for vocoding or bypassing a voice/data packet received from a radio channel interval, based on the operational mode control signal of the controller; a random number generator for generating a random number based on the  
10 scrambling key feeding control signal of the controller; a sync signal transmitter for generating a sync signal based on the sync signal generation control signal of the controller, and sending the generated sync signal to a cable channel interval; and a scrambler for scrambling a vocoded PCM (pulse code modulation) signal or a bypassed voice/data packet of the operational mode processor using the random number generated  
15 from the random number generator and, after complete transmission of the sync signal, sending the scrambled PCM signal or voice/data packet to the cable channel interval.

In another aspect of the present invention, there is provided a device for descrambling voice and data in a mobile communication system including: a sync signal detector for detecting a sync signal from an scrambled signal received from a cable  
20 channel interval; a controller for generating a descrambling control signal, an operational mode control signal, and a descrambling key feeding control signal, upon detection of the sync signal at the sync signal detector; a random number generator for generating a random number based on the descrambling key feeding control signal of the controller; a



descrambler for descrambling the scrambled signal received from the cable channel interval using the random number generated from the random number generator, based on the descrambling control signal of the controller; and an operational mode processor for vocoding a descrambled PCM signal of the descrambler into a packet or bypassing a voice/data packet, based on the operational mode control signal of the controller, and then sending the vocoded PCM signal or the bypassed voice/data packet to a radio channel interval.

In further another aspect of the present invention, there is provided a device for scrambling/descrambling voice and data in a mobile communication system including:

10 an operational mode processor for vocoding or bypassing a voice/data packet received from a radio channel interval based on a received operational mode signal, and vocoding or bypassing a descrambled PCM signal or packet based on the operational mode signal; a random number generator for generating a random number based on a received scrambling and descrambling key feeding control signal; a sync signal transmitter for

15 generating a sync signal based on a received control signal, and sending the generated sync signal to a cable channel interval; a scrambler for scrambling the vocoded PCM signal or the bypassed voice/data packet of the operational mode processor using the random number generated from the random number generator and, after complete transmission of the sync signal, sending the scrambled PCM signal or voice/data packet

20 to the cable channel interval; a sync signal detector for detecting a sync signal from the scrambled signal received from the cable channel interval; a descrambler for descrambling the scrambled signal received from the cable channel interval using the random number generated from the random number generator, based on a received

descrambling control signal; and a controller for generating the descrambling control signal to the descrambler, the scrambling and descrambling key feeding control signal, and the sync signal generation control signal, upon detection of the sync signal at the sync signal detector.

5           In still further another aspect of the present invention, there is provided a method for scrambling voice and data in a mobile communication system including the steps of: vocoding or bypassing a voice/data packet received from a radio channel interval based on a received operational mode signal; generating a defined random number based on scrambling key information; generating a sync signal and sending the  
10       generated sync signal to a cable channel interval; and upon complete transmission of the sync signal, scrambling the mode-processed signal (including a PCM signal, or bypassed voice/data packet) using the random number and sending the scrambled signal to the cable channel interval.

          In still further another aspect of the present invention, there is provided a  
15       method for descrambling voice and data in a mobile communication system including the steps of: receiving an scrambled signal from a cable channel interval; upon receiving the scrambled signal, detecting a sync signal from the scrambled signal; upon detection of the sync signal, generating a random number based on a descrambling key signal; descrambling the scrambled signal using the random number; and vocoding a  
20       descrambled PCM signal or bypassing a descrambled packet based on an operational mode signal, and sending the vocoded PCM signal or the bypassed packet to a radio channel interval.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a diagram for explaining interval-based transmission pattern between mobile stations in a general mobile communication system;

Fig. 2 presents the bypassed packet pattern of a vocoder in a general mobile communication system, wherein Fig. 2a shows the format of a bypassed voice packet and

5 Fig. 2b shows the format of a bypassed data packet;

Fig. 3 is a schematic block diagram of the vocoding device based on an operational mode in a mobile communication system according to prior art;

Fig. 4 is a schematic block diagram of a device for scrambling/descrambling voice and data in a mobile communication system according to the present invention; and

10 Figs. 5a and 5b are flow charts for explaining a method for scrambling/descrambling voice and data in a mobile communication system according to the present invention.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

Hereinafter, a detailed description will be given to a device and method for  
15 scrambling/descrambling voice and data in a mobile communication system according to the present invention with reference to the accompanying drawings.

First, in the present invention, there are three patterns of the communication signal delivered on cable channels according to the operational mode of a system vocoder during communication between mobile stations. That is, in the voice  
20 communication, the transmission data has a pattern of PCM signal when the system vocoder operates in a normal vocoding mode, and bypassed voice packet when the system vocoder operating in a voice packet bypass mode.

Meanwhile, in the data communication, the system vocoder operates in a data

packet bypass mode and the transmission data has a pattern of bypassed data packet on the cable channels.

The present invention enables a scrambling/descrambling operation for all patterns of the transmission data.

5           Fig. 4 is a schematic block diagram of a vocoding system for scrambling/descrambling voice/data in a mobile communication system according to the present invention.

As illustrated in the figure, the vocoding system comprises: an upper processor 30 for providing operational mode information and scrambling key information; an  
10           operational mode processor 41 for processing voice/data packet received on a radio channel "A" from an originating mobile station in a vocoding mode or a bypass mode based on the operational mode information received from the upper processor 30, or processing descrambled signals as a packet in the vocoding mode or the bypass mode, and sending the processed packet to a target mobile station via a radio channel "B"; a  
15           controller 42 for storing the scrambling key information received from the upper processor 30, and generating a scrambling key information storage control signal, a scrambling key information output control signal, a sync signal transmission control signal and a switching control signal to output the stored scrambling key; and a scrambling key seed block 45 for storing the scrambling key information received from  
20           the upper processor based on the storage control signal from the controller 42, and outputting the stored scrambling key information based on the output control signal.

The vocoding system further comprises: a first switching block 43 for switching the operational mode from a normal mode to a scrambling mode based on the control

signal received from the controller 42; a random number generator 46 for generating a random number based on the scrambling key information received from the scrambling key seed block 45; a scrambler 47 for scrambling the packet or PCM signal mode-processed (i.e., vocoded or bypassed) at the operational mode processor 41 based on the  
5 random number generated from the random number generator 46; a sync signal transmitter 44 for generating and sending a sync signal based on the sync signal transmission control signal received from the controller 42; and a second switching block 48 for sending the sync signal received from the sync signal transmitter 44 and then switching the scrambled signal from the scrambler 47, thereby sending the scrambled  
10 data to an exchange via a cable channel "C".

The vocoding system further comprises: a sync signal detector 49 for detecting a sync signal from the scrambled signal received via a cable channel "D"; a third switching block 50 for switching the operational mode from a normal mode to a descrambling mode based on the control signal of the controller 42, upon detection of the sync signal at  
15 the sync signal detector 49; and a descrambler 51 for descrambling the scrambled signal received based on the switching operation of the third switching block 50, and sending the descrambled signal to the operational mode processor 41.

A detailed description will now be given to an operation of the above-structured voice/data scrambling/descrambling device in a mobile communication system according  
20 to the present invention.

First, the vocoder 40 receives operational mode information "E" and scrambling key information "F" from the upper processor 30. Then, the operational mode processor 41 and the controller 42 in the vocoder 40 generate various control signals.

That is, the controller 42 stores the scrambling key in the scrambling key seed block 45 and outputs the stored scrambling key read out from the scrambling key seed block 45 to the random number generator 46. The controller 42 also switches the first switching block 43 from stage “a” to stage “g”.

5        The random number generator 46 generates a random number based on the scrambling key received from the scrambling key seed block 45 and applies the generated random number to the scrambler 47.

According to the switching operation of the first switching block 43, the scrambler 47 scrambles the bypassed packet or vocoded PCM signal received from the operational mode processor 41 based on the random number received from the random number generator 46, and outputs the scrambled packet or PCM signal to the second switching block 48.

The controller 42 provides a control signal to the sync signal transmitter 44 and a switching control signal to the second switching block 48 so as to send the sync signal of the sync signal transmitter 44 to the cable channel interval. Once the sync signal is sent to the cable channel interval, the controller 42 switches from the second switching block 48 to the scrambler 47 to send the scrambled signal from the scrambler 47 to the cable channel interval.

Here, the sync signal is transmitted once prior to sending the scrambled signal for the first frame to the cable channel interval, and never transmitted for all subsequent frames.

Meanwhile, upon receiving scrambled data in the cable channel interval, the sync signal detector 49 of the vocoder 40 detects the sync signal from the received scrambled

signal and applies the detection result to the controller 42.

Once the sync signal detector 49 detects the sync signal, the controller 42 switches the third switching block 50 from stage “d” to stage “i”.

Consequently, the scrambled signal undergoes the reverse processing of the scrambling, i.e., the signal is descrambled based on the random number output from the random number generator 46. Thus descrambled packet or PCM signal is applied to the operational mode processor 41.

The operational mode processor 41 performs a vocoding or bypass operation based on the operational mode information received from the upper processor 30 and sends the bypassed packet or vocoded PCM signal to the radio channel interval.

A further detailed description will now be given to the scrambling and descrambling operations.

Once the vocoder 40 receives operational mode information and scrambling key information from the upper processor 30, the operational mode processor 41 and the controller 42 generate control signals from the information. That is, the controller 42 stores a scrambling key in the scrambling key seed block 45 and outputs the stored scrambling key to the random number generator 46.

The random number generator 46 generates a random number based on the scrambling key received from the scrambling key seed block 45. The random number is used as information for scrambling or descrambling the input/output communication signals of the vocoder 40. The information corresponds to the positional information of the input/output communication signals of the vocoder 40, the positional information being fed into the scrambler 47 and the descrambler 51.

The scrambler 47 uses the positional information generated from the random number generator 46 to rearrange the position of the communication signal “g” output from the operational mode processor 41 in the unit of bits or bytes. Here, the scrambling performance is higher when rearranging the communication signal in the unit of bits rather than in the unit of bytes. The scrambler 47 combines the rearranged signal “h” with the sync signal generated from the sync signal transmitter 44 and outputs the composite signal to an output “C” of the vocoder 40, thereby sending the scrambled signal on the cable channel.

The descrambler 51 uses the positional information generated from the random number generator 46 to rearrange the scrambled signal “d” on the cable channel interval “D” by the reverse process of the scrambling shown in Table 1, thus descrambling the original signal “j”. An example of the descrambling process will now be described with reference to Table 1.

[Table 1]

Original Position	0	1	2	3	4	5	6	7	8	9
Communication Signal	X0	X1	X2	X3	X4	X5	X6	X7	X8	X9
Random Number	1	3	5	7	2	9	8	4	6	0
Rearranged Signal	X0	X3	X5	X7	X2	X9	X8	X4	X6	X0

Expediently, it is assumed that the communication signal “g” is rearranged (scrambled) in the unit of 10 bytes, generating ten random numbers “k” ranging from position 0 to position 9. Once a random number is generated as shown in Table 1, in which the first random number is “1”, the communication signal X1 at position “1” is



shifted to the first position (i.e., position “0”). As the second random number is “3”, the communication signal at position “3”, i.e., X3 is disposed at the second position (i.e., position “1”). Similarly, as the final random number is “0”, the communication signal X0 at position “0” is moved to position “9”. This procedure obtains the rearranged signals as  
5 listed in the bottom row, which signals are scrambled signals.

The descrambling process is a reverse procedure of the scrambling process, which means that the original communication signals can be easily rearranged.

The scrambling start time must be in conformity with the descrambling start time so that the respective vocoders at the transmitter and the receiver of the system can  
10 descramble the scrambled signals accurately. That is, considerations of transmission delay of the communication signal in the cable channel interval between the system vocoders are important in descrambling the signals. The methods for solving this problem may depend on the design and configuration of the system. The present invention employs a descrambling method applicable to any system configuration, in  
15 which method the sync signal transmitter 44 sends the sync information for the operating time of the scrambler 47 and the descrambler 51 to the second switching block 48 through the cable channels before the scrambler 47 transmits the scrambled signal.

Simultaneously, the descrambler 51 descrambles the scrambled signal by the above-stated descrambling method after detection of the sync signal received from the  
20 cable channel “D”.

This eliminates inconformity of the driving time between the scrambler 47 and the descrambler 51 that may be caused due to transmission delay of the communication signal between the vocoders at the transmitter and the receiver on the cable channel,

thereby enabling accurate scrambling of the communication signal and descrambling the scrambled signal using the same scrambling key. Here, the sync information has a defined pattern previously negotiated between the system vocoders.

A stepwise description will be given to a voice/data scrambling and descrambling  
5 method for a mobile communication system according to the present invention with reference to Fig. 5.

The voice/data scrambling method in a mobile communication system will be described in connection with Fig. 5a.

First, step S101 mode-processes the voice packet or data packet received from the  
10 radio channel interval based on the operational mode information supplied by the upper processor 30. That is, the voice packet is vocoded into PCM data, or the voice/data packet is bypassed, based on the corresponding operational mode.

Step S102 generates a random number based on the scrambling key information applied from the upper processor 30.

15 Step S103 generates a sync signal and sends the generated sync signal to the cable channel interval. After completion of the transmission of the sync signal, step S104 scrambles the mode-processed signal (e.g., PCM data, or bypassed voice packet or data packet) using the random number.

Step S105 sends the scrambled signal in the cable channel interval.

20 Next, a stepwise description will be given to a method for descrambling the scrambled signal received from the cable channel interval with reference to Fig. 5b.

First, step S201 determines whether a scrambled signal is received from the cable channel interval.

Once the scrambled signal is received, step S202 detects a sync signal from the scrambled signal.

Step S203 determines whether the sync signal is detected, and upon detection of the sync signal, step S204 generates a defined random number based on a scrambling key  
5 supplied.

Subsequently, step S205 descrambles the received scrambled signal based on the random number, and step S206 mode-processes the descrambled signal, i.e., PCM or packet based on the operational mode information, thereafter sending the mode-processed packet to the radio channel interval. Here, the corresponding mode enables an  
10 operation for converting the descrambled PCM signal to a packet or bypassing the scrambled packet.

As described above, the “device and method for scrambling/descrambling voice/data in a mobile communication system” according to the present invention involves vocoding or bypassing the signal received from a radio channel interval,  
15 scrambling the vocoded or bypassed signal using a random number, sending the scrambled signal to a cable channel interval, descrambles the scrambled signal received from the cable channel interval, vocoding or bypassing the descrambled signal, and sending the vocoded or bypassed signal to the radio channel interval, thereby dramatically security of the data in the cable channel interval between the system  
20 vocoders and preventing overhearing of the voice.

Furthermore, the application of the present invention is expandable to the radio channel interval between the mobile station and the vocoder, thus providing security of data over all channels.

It is to be noted that like reference numerals denote the same components in the drawings, and a detailed description of generally known function and structure of the present invention will be avoided lest it should obscure the subject matter of the present invention.

5

**WHAT IS CLAIMED IS:**

1. In a voice/data vocoding device for a mobile communication system, a device for scrambling voice and data in the mobile communication system comprising:

5 a controller for generating an operational mode control signal to control an operational mode of the voice and data, a scrambling key feeding control signal to control data scrambling, and a sync signal generation control signal;

an operational mode processor for vocoding or bypassing a voice/data packet received from a radio channel interval, based on the operational mode control signal of  
10 the controller;

a random number generator for generating a random number based on the scrambling key feeding control signal of the controller;

a sync signal transmitter for generating a sync signal based on the sync signal generation control signal of the controller, and sending the generated sync signal to a  
15 cable channel interval; and

a scrambler for scrambling a vocoded PCM (pulse code modulation) signal or a bypassed voice/data packet of the operational mode processor using the random number generated from the random number generator and, after complete transmission of the sync signal, sending the scrambled PCM signal or voice/data packet to the cable channel  
20 interval.

2. The device as claimed in claim 1, further comprising a switching block switched to the sync signal generator under the control of the controller to send the sync

signal generated from the sync signal generator to the cable channel interval and, after complete transmission of the sync signal, switched to the scrambler according to the control signal of the controller to send the scrambled signal to the cable channel interval.

5           3.       The device as claimed in claim 1, further comprising a scrambling key feeder for feeding the stored scrambling key to the random number generator based on the control signal of the controller.

10           4.       The device as claimed in claim 1, wherein the random number generated from the random number generator includes positional information for scrambling the vocoded PCM signal or the bypassed voice/data packet of the operational mode processor.

15           5.       In a voice/data vocoding device for a mobile communication system, a device for descrambling voice and data in the mobile communication system comprising:

          a sync signal detector for detecting a sync signal from an scrambled signal received from a cable channel interval;

          a controller for generating a descrambling control signal, an operational mode control signal, and a descrambling key feeding control signal, upon detection of the sync  
20    signal at the sync signal detector;

          a random number generator for generating a random number based on the descrambling key feeding control signal of the controller;

          a descrambler for descrambling the scrambled signal received from the cable

channel interval using the random number generated from the random number generator,  
based on the descrambling control signal of the controller; and

an operational mode processor for vocoding a descrambled PCM signal of the  
descrambler into a packet or bypassing a voice/data packet, based on the operational  
5 mode control signal of the controller, and then sending the vocoded PCM signal or the  
bypassed voice/data packet to a radio channel interval.

6. The device as claimed in claim 5, further comprising a switching block  
for switching the scrambled signal received from the cable channel interval to the  
10 descrambler, based on the control signal of the controller.

7. The device as claimed in claim 5, further comprising a descrambling key  
feeder for feeding the stored descrambling key to the random number generator based on  
the control signal of the controller.  
15

8. The device as claimed in claim 5, wherein the random number generated  
from the random number generator includes positional information for descrambling the  
PCM signal or voice/data packet received from the cable channel interval.

9. In a voice/data vocoding device for a mobile communication system, a  
device for scrambling/descrambling voice and data in the mobile communication system  
comprising:

an operational mode processor for vocoding or bypassing a voice/data packet

received from a radio channel interval based on a received operational mode signal, and vocoding or bypassing a descrambled PCM signal or packet based on the operational mode signal;

5 a random number generator for generating a random number based on a received scrambling and descrambling key feeding control signal;

a sync signal transmitter for generating a sync signal based on a received control signal, and sending the generated sync signal to a cable channel interval;

10 a scrambler for scrambling the vocoded PCM signal or the bypassed voice/data packet of the operational mode processor using the random number generated from the random number generator and, after complete transmission of the sync signal, sending the scrambled PCM signal or voice/data packet to the cable channel interval;

a sync signal detector for detecting a sync signal from the scrambled signal received from the cable channel interval;

15 a descrambler for descrambling the scrambled signal received from the cable channel interval using the random number generated from the random number generator, based on a received descrambling control signal; and

a controller for generating the descrambling control signal to the descrambler, the scrambling and descrambling key feeding control signal, and the sync signal generation control signal, upon detection of the sync signal at the sync signal detector.

20

10. The device as claimed in claim 9, further comprising a descrambling key feeder for feeding the stored scrambling and descrambling keys to the random number generator based on the control signal of the controller.



11. In a voice/data vocoding method for a mobile communication system, a method for scrambling voice and data in the mobile communication system comprising the steps of:

5           vocoding or bypassing a voice/data packet received from a radio channel interval based on a received operational mode signal;

          generating a defined random number based on scrambling key information;

          generating a sync signal and sending the generated sync signal to a cable channel interval; and

10          upon complete transmission of the sync signal, scrambling the mode-processed signal (including a PCM signal, or bypassed voice/data packet) using the random number and sending the scrambled signal to the cable channel interval.

12. In a voice/data vocoding method for a mobile communication system, a method for descrambling voice and data in the mobile communication system comprising the steps of:

          receiving an scrambled signal from a cable channel interval;

          upon receiving the scrambled signal, detecting a sync signal from the scrambled signal;

20          upon detection of the sync signal, generating a random number based on a descrambling key signal;

          descrambling the scrambled signal using the random number; and

          vocoding a descrambled PCM signal or bypassing a descrambled packet based

on an operational mode signal, and sending the vocoded PCM signal or the bypassed packet to a radio channel interval.

## ABSTRACT OF THE DISCLOSURE

The device and method for scrambling/descrambling voice/data in a mobile communication system involves vocoding or bypassing a signal received from a radio channel interval, scrambling the vocoded or bypassed signal using a random number, sending the scrambled signal to a cable channel interval, descrambles the scrambled signal received from the cable channel interval, vocoding or bypassing the descrambled signal, and sending the vocoded or bypassed signal to the radio channel interval, thereby dramatically security of the data in the cable channel interval between the system vocoders and preventing overhearing of the voice.

10

"Express Mail" mailing label number EL67489748XUS  
Date of Deposit November 21, 2002  
I hereby certify that this paper or fee is being deposited  
with the United States Postal Service "Express Mail Post  
Office to Addressee" service under 37 CFR 1.10 on the  
date indicated above and is addressed to: Commissioner  
of Patents and Trademarks, Washington, D.C. 20231.  
Grant Miles  
(printed name)  
Grant Miles  
(signature)

FIG. 1




FIG. 2a



FIG. 2b



FIG. 3




FIG. 4




FIG. 5a







FIG. 5b



MERCHANT &amp; GOULD P.C.

## United States Patent Application

## COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: DEVICE AND METHOD FOR SCRAMBLING/DESCRAMBLING VOICE AND DATA FOR MOBILE COMMUNICATION SYSTEM

The specification of which

a. ☒ is attached hereto

b. ☐ was filed on \_\_\_\_\_ as application serial no. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable) (in the case of a PCT-filed application) described and claimed in international no. \_\_\_\_\_ filed \_\_\_\_\_ and as amended on \_\_\_\_\_ (if any), which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (attached hereto).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

a. ☐ no such applications have been filed.

b. ☒ such applications have been filed as follows:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
Republic of Korea	1999-58711	17/12/ 1999	
ALL FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Albrecht, John W.	Reg. No. 40,481	Kowalchyk, Alan W.	Reg. No. 31,535
Ali, M. Jeffer	Reg. No. 46,359	Kowalchyk, Katherine M.	Reg. No. 36,848
Anderson, Gregg I.	Reg. No. 28,828	Lacy, Paul E.	Reg. No. 38,946
Batzli, Brian H.	Reg. No. 32,960	Larson, James A.	Reg. No. 40,443
Beard, John L.	Reg. No. 27,612	Liepa, Mara E.	Reg. No. 40,066
Berns, John M.	Reg. No. 43,496	Lindquist, Timothy A.	Reg. No. 40,701
Black, Bruce E.	Reg. No. 41,622	Lycke, Lawrence E.	Reg. No. 38,540
Branch, John W.	Reg. No. 41,633	McAuley, Steven A.	Reg. No. 46,084
Bremer, Dennis C.	Reg. No. 40,528	McDonald, Daniel W.	Reg. No. 32,044
Bruess, Steven C.	Reg. No. 34,130	McIntyre, Jr., William F.	Reg. No. 44,921
Byrne, Linda M.	Reg. No. 32,404	Mueller, Douglas P.	Reg. No. 30,300
Campbell, Keith	Reg. No. P-46,597	Pauly, Daniel M.	Reg. No. 40,123
Carlson, Alan G.	Reg. No. 25,959	Phillips, Bryan K.	Reg. No. P-46,990
Caspers, Philip P.	Reg. No. 33,227	Phillips, John B.	Reg. No. 37,206
Chiapetta, James R.	Reg. No. 39,634	Plunkett, Theodore	Reg. No. 37,209
Clifford, John A.	Reg. No. 30,247	Prendergast, Paul	Reg. No. 46,068
Daignault, Ronald A.	Reg. No. 25,968	Pytel, Melissa J.	Reg. No. 41,512
Daley, Dennis R.	Reg. No. 34,994	Qualey, Terry	Reg. No. 25,148
Dalglish, Leslie E.	Reg. No. 40,579	Reich, John C.	Reg. No. 37,703
Daulton, Julie R.	Reg. No. 36,414	Reiland, Earl D.	Reg. No. 25,767
DeVries Smith, Katherine M.	Reg. No. 42,157	Schmaltz, David G.	Reg. No. 39,828
DiPietro, Mark J.	Reg. No. 28,707	Schuman, Mark D.	Reg. No. 31,197
Edell, Robert T.	Reg. No. 20,187	Schumann, Michael D.	Reg. No. 30,422
Epp Ryan, Sandra	Reg. No. 39,667	Scull, Timothy B.	Reg. No. 42,137
Glance, Robert J.	Reg. No. 40,620	Sebald, Gregory A.	Reg. No. 33,280
Goggin, Matthew J.	Reg. No. 44,125	Skoog, Mark T.	Reg. No. 40,178
Golla, Charles E.	Reg. No. 26,896	Spellman, Steven J.	Reg. No. 45,124
Gorman, Alan G.	Reg. No. 38,472	Stoll-DeBell, Kirstin L.	Reg. No. 43,164
Gould, John D.	Reg. No. 18,223	Sumner, John P.	Reg. No. 29,114
Gregson, Richard	Reg. No. 41,804	Swenson, Erik G.	Reg. No. 45,147
Gresens, John J.	Reg. No. 33,112	Tellekson, David K.	Reg. No. 32,314
Hamer, Samuel A.	Reg. No. P-46,754	Trembath, Jon R.	Reg. No. 38,344
Hamre, Curtis B.	Reg. No. 29,165	Underhill, Albert L.	Reg. No. 27,403
Harrison, Kevin C.	Reg. No. P-46,759	Vandenburgh, J. Derek	Reg. No. 32,179
Hertzberg, Brett A.	Reg. No. 42,660	Wahl, John R.	Reg. No. 33,044
Hillson, Randall A.	Reg. No. 31,838	Weaver, Karrie G.	Reg. No. 43,245
Holzer, Jr., Richard J.	Reg. No. 42,668	Welter, Paul A.	Reg. No. 20,890
Johnston, Scott W.	Reg. No. 39,721	Whipps, Brian	Reg. No. 43,261
Kadievitch, Natalie D.	Reg. No. 34,196	Wickhem, J. Scot	Reg. No. 41,376
Karjeker, Shaukat	Reg. No. 34,049	Williams, Douglas J.	Reg. No. 27,054
Kastelic, Joseph M.	Reg. No. 37,160	Witt, Jonelle	Reg. No. 41,980
Kettelberger, Denise	Reg. No. 33,924	Wu, Tong	Reg. No. 43,361
Keys, Jeramie J.	Reg. No. 42,724	Xu, Min S.	Reg. No. 39,536
Knearl, Homer L.	Reg. No. 21,197	Zeuli, Anthony R.	Reg. No. 45,255

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Merchant & Gould P.C. to the contrary.

Please direct all correspondence in this case to Merchant & Gould P.C. at the address indicated below:

Merchant & Gould P.C.  
P.O. Box 2903  
Minneapolis, MN 55402-0903

**\*23552\***

**23552**

PATENT TRADEMARK OFFICE

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> PARK	<b>First Given Name</b> Jung	<b>Second Given Name</b> Jin
0	<b>Residence &amp; Citizenship</b>	<b>City</b> Ichon	<b>State or Foreign Country</b> Republic of Korea	<b>Country of Citizenship</b> Republic of Korea
1	<b>Post Office Address</b>	<b>Post Office Address</b> San 136-1, Ami-ri, Bubal-eub	<b>City</b> Ichon-city	<b>State &amp; Zip Code/Country</b> Kyungki-do, Republic of Korea
<b>Signature of Inventor 201:</b>			<b>Date:</b>	
Jung Jin PARK			November 11, 2000	

#### § 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;
- or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
  - (i) Opposing an argument of unpatentability relied on by the Office, or
  - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.